

Frames		Single telescopic						Double telescopic			Extend			
		Monoblock			Monoblock2 Comfort			Mixed Monoblock2 Comfort	Monoblock	Monoblock2 Comfort	Extend 6			
Width		4 m 50			4 m 50			4 m 50	4 m 50	4 m 50	4 m 50	3 m 00/ 4 m 50		
Transport width		3 m 50			3 m 50			3 m 50	3 m 00	3 m 00	3 m 00*	3 m 00		
Number of metering units		6	7	8	6	7	8	7	6	6	7	6		
Inter-row spacings (cm)		75/80	55/60	45/49	75/80	50/55/60	49	75 or 80 (6 rows) 56,2 or 60 (7 rows)	75/80	75/80	55/60/ 65/70	45-50-55- 60-65-70- 75-80		
Turbofan		Drive by PTO – 540 rpm in standard version,												
Tyres		2 x (6.5x80x15)			2 x (26x12)			2 x (26 x 12)	2 x (6.5x80x15)	2 x (26x12)		2 x (26x12)		
Drive	Mechanical	Standard		○ 1			-			○ 1		-		
		Lateral		-			● 1			-		● 1		
		EasyGear		● 1			-			● 1		-		
Electric		○	Please consult us		○	Please consult us		○	○	○	Please consult us			
Hydraulic row markers		●			●			●		●		●		
Fertilizer	Standard		○ 2 x 270 l.	-	-	-		○ 2 x 270 l.		-		-		
	High capacity		○ 980 l.	-	-	○ 1 x 680 l. or 1 x 1030 l.		○ 1 x 680 l. or 1 x 1030 l.		○ 980 l.	○ 1 x 680 l. or 1 x 1030 l.		○ 1020 l.	
	Front-mounted Standard		○			○			○		○		○	
	Front-mounted DUO		-			-			-		-		-	
Microsem	Insecticide		○			○			○		○		○	
	Helicide		○			○			○		○		○	
Hectare counter		○			○			○		○		○		
Seed monitors		○			○			○		○		○		
Row cut-off system		○			○			○		○		○		
Lighting kit		○			○			○		○		○		
Weight planter only		1300 kg	1425 kg	1550 kg	1500 kg	1625 kg	1750 kg	1625 kg	1350 kg	1550 kg	1675 kg	1700 kg		

● : Standard ○ : On option - : Not possible * Depending on the equipment For other models, special inter-row spacings and other crops, please consult us.

MAIN MONOSHOX NG PLUS M SEED DISCS

Type of seed	Standard discs delivered	Number of holes	Diameter of holes	Distances on the row		Other possibilities, number and Ø of holes
				Standard seed spacing gearbox	EasyGear seed spacing gearbox	
Maize	DC 3050	30	5 mm	7,2 to 21,3 cm	10,2 to 19,6 cm	18 - 24 - 36 and Ø 4,5 - 6 mm
Sunflower	DC 2425 DC 1825	24 18	2,5 mm	9,1 to 26,6 cm 12,1 to 35,5 cm	12,7 to 24,5 cm 16,9 to 32,7 cm	
Sugarbeet	DC 3020	30	2 mm	7,2 to 21,3 cm	10,2 to 19,6 cm	24
Beans	DC 6045 DC 6035	60	4,5 mm 3,5 mm	3,6 to 10,7 cm	5,1 to 9,8 cm	Ø 2,5 mm
Soya - Peas	DC 6045	60	4,5 mm	3,6 to 10,7 cm	5,1 to 9,8 cm	
Rapeseed	DC 7212	72	1,2 mm	3,0 to 8,9 cm	4,2 to 8,2 cm	36 - 60 - 120
Cabbage	DC 3612	36	1,2 mm	6,0 to 17,8 cm	8,5 to 16,4 cm	72 - 120
Sorghum	DC 7222	72	2,2 mm	3,0 to 8,9 cm	4,2 to 8,2 cm	36
Kidney beans	DC 3060	30	6 mm	7,2 to 21,3 cm	10,2 to 19,6 cm	Ø 5 - 6,5 mm
Peanut	DC 3065	30	6,5 mm	7,2 to 21,3 cm	10,2 to 19,6 cm	36 and Ø 5,5 - 6 mm

FEATURES



The precision Planter specialist

Folding															
Extend 6/7	Double bar			TFC Floating	TFC Rigid	TFC2 Comfort					Mixed TFC2 Comfort		CRT		
3 m 10/ 4 m 50	6 m 00		7 m 00	6 m 00	6 m 00	6 m 00					6 m 00		9 m 00		
3 m 10	3 m 00		3 m 50	3 m 00	3 m 00	3 m 00*					3 m 00*		3 m 00*	3 m 50*	
7	8	9	11	12	8	8	8	9	11	12	16	11	12	12	13
75-80 (6 rows) 55-60 (7 rows)	75/80	60	60	45/50	75/80	75/80	75/80	55/60/65	55	45/50	37,5	75 or 80 (8 rows) 55 (11 rows)	75 or 80 (8 rows) 45 or 50 (12 rows)	70/75/80	60
450 or 1000 rpm on option - Hydraulic drive on option, universal joint on option															
2 x (26x12)	4 x (6.5x80x15)			4 x (26x12)	2 x (26x12)	4 x (26x12)					4 x (26x12)		4 x (6.5x80x15)		
-	○ 3			○ 3	-	○ 3					○ 3		-		
● 1	-			-	● 1	-					-		-		
-	● 3			● 3	-	● 3					● 3		● 3		
○	○			Please consult us	Please consult us	○					Please consult us	○	○		
●	●			●	●	●					●		●		
-	○ 4 x 175 l.			-	-	-					-		○ 4 x 270 l.		
-	-			○ 1500 l.	○ 1500 l.	-					-		-		
○	○			-	-	○					○		○		
-	○			-	-	○					○		○		
○	○			○	○	○					○		○		
○	○			○	○	○					○		○		
○	○			○	○	○					○		○		
○	○			○	○	○					○		○		
○	○			○	○	○					○		○		
○	○			○	○	○					○		○		
○	○			○	○	○					○		○		
1850 kg	2250 kg	2350 kg	2600 kg	2550 kg	2900 kg (with fertilizer)	2850 kg (with fertilizer)	2700 kg	2800 kg	3000 kg	3100 kg	3500 kg	3050 kg	3150 kg	3500 kg	3500 kg

MONOSHOX NG PLUS M METERING UNIT EQUIPMENT

Metering unit type	Maize	Sunflower	Beans	Sugarbeet	Rapeseed
52L hopper	●	●	●	○ 1)	● 1)
16L hopper	-	-	-	●	○
Gauge wheels 110 mm	●	●	●	○ 1)	● 1)
Gauge wheels 50 mm	○	○	○	●	○
Standard clod removers	●	●	●	-	● 1)
Narrow clod removers	○	○	○	●	○
Clod removers with flexible bracket	○	○	○	○	○
Disc on metering unit	○	○	○	○	○
Trash wheel	○	○	○	○ 1)	○ 1)
Monoshox.EU Suspension with shock absorber	●	●	●	●	●
Long tip	●	●	●	○	○
Long tip, short wings	○	○	○	●	●
PRO Wheel	○	○	●	●	●
Press wheels 2"	●	●	●	●	●
Press wheels 1"	○	○	○	○	○

● : Standard
○ : On option
- : Not possible
1) Depending on inter-row spacings and frames
For other models and other crops, please consult us.