

Maxidrill 3010



Maxidrill 4010



Maxidrill W4010



Maxidrill W6010



Working width	3m	4m	4m	6m
Transport width	3m	4m	3m	3m
Distribution	Pneumatic	Pneumatic	Pneumatic	Pneumatic
Hopper capacity	3 000 liters	3 000 liters	3 000 liters	4 100 liters
Volume repartition (with Fertisem)	60/40 : 1 760 l + 1 240 l 45/55 : 1 440 l + 1 560 l 95/5 : 2 900 l + 100 l	60/40 : 1 760 l + 1 240 l 45/55 : 1 440 l + 1 560 l 95/5 : 2 900 l + 100 l	60/40 : 1 760 l + 1 240 l 45/55 : 1 440 l + 1 560 l 95/5 : 2 900 l + 100 l	60/40 : 2 450 l + 1 650 l 45/55 : 1 800 l + 2 300 l 95/5 : 4 000 l + 100 l
Pro Hopper capacity	120 liters	120 liters	120 liters	120 liters
Row spacing	15 cm	14,3 cm	14,3 cm	15 cm
Weight (without options)	4 200 kg	5 550 kg	6 750 kg	8 350 kg
Number of rows	20 rows	28 rows	28 rows	40 rows
Number of discs	24 discs	32 discs	32 discs	48 discs
Power required	from 105 to 150 hp	from 120 to 180 hp	from 140 to 200 hp	from 210 to 300 hp
Tire dimensions axle (series)	-	-	600/50 R22,5	700/40 R22,5
Number of distributors DE / SE	1 SA + free return oil line for fan 1 DA for setting and lifting 1 SA for markers	1 SA + free return oil line for fan 1 DA for setting and lifting 1 SA for markers	1 SA + free return oil line for fan 1 DA for folding 1 DA for markers 1 DA for axle	1 SA + free return oil line for fan 1 DA for folding 1 DA for markers 1 DA for axle
Filling height	248 cm	260 cm	260 cm	290 cm